

## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: IF Maxid Silage L

Other means of identification:

**UFI:** FW22-E0CY-H00N-SFHW

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Additive for fodder (animal feed) Relevant uses (Industrial user): Additive for fodder (animal feed)

For Professional users/Industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Indufarm nv

Leon Bekaertstraat 5

8770 - Ingelmunster Belgium Phone: +32(0)51624245 contact@indufarm.com www.indufarm.com

1.4 Emergency telephone number: +32(0)70245245 Mon-Sun 24h

## SECTION 2: HAZARDS IDENTIFICATION \*\*

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1B: Skin corrosion, Category 1B, H314 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

#### Dange





#### **Hazard statements:**

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

STOT SE 3: H335 - May cause respiratory irritation.

#### **Precautionary statements:**

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

- CONTINUED ON NEXT PAGE -

#### **Supplementary information:**

EUH071: Corrosive to the respiratory tract.

UFI: FW22-E0CY-H00N-SFHW

## 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

Page 1/13

<sup>\*\*</sup> Changes with regards to the previous version



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substance:

Not relevant

#### 3.2 Mixture:

**Chemical description:** EU-approved feed blend designed to enhance taste, texture, or preservation

#### **Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	j	Concentration
CAS:	79-09-4	propionic acid(1)		Self-classified	
EC: Index: REACH:	201-176-3 607-089-00-0 : 01-2119486971-24- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; Skin Corr. 1B: H314; STOT SE 3: H335 - Danger		25 - <50 %
CAS:	64-18-6	Formic acid(1)		Self-classified	
Index: REACH:	200-579-1 607-001-00-0 01-2119491174-37- XXXX	Regulation 1272/2008	Acute Tox. 3: H331; Acute Tox. 4: H302; Flam. Liq. 3: H226; Skin Corr. 1A: H314; EUH071 - Danger		25 - <50 %
CAS:	64-19-7	Acetic acid(2)		ATP CLP00	
Index: (	200-580-7 607-002-00-6 01-2119475328-30- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226; Skin Corr. 1A: H314 - Danger	<b>⋄</b> ❖	<1 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification	Specific concentration limit
propionic acid CAS: 79-09-4 EC: 201-176-3	% (w/w) >=25: Skin Corr. 1B - H314 10<= % (w/w) <25: Skin Irrit. 2 - H315 % (w/w) >=25: Eye Dam. 1 - H318 10<= % (w/w) <25: Eye Irrit. 2 - H319 % (w/w) >=10: STOT SE 3 - H335
Formic acid CAS: 64-18-6 EC: 200-579-1	% (w/w) >=90: Skin Corr. 1A - H314 10<= % (w/w) <90: Skin Corr. 1B - H314 2<= % (w/w) <10: Skin Irrit. 2 - H315 % (w/w) >=10: Eye Dam. 1 - H318 2<= % (w/w) <10: Eye Irrit. 2 - H319
Acetic acid CAS: 64-19-7 EC: 200-580-7	% (w/w) >=90: Skin Corr. 1A - H314 25<= % (w/w) <90: Skin Corr. 1B - H314 10<= % (w/w) <25: Skin Irrit. 2 - H315 % (w/w) >=25: Eye Dam. 1 - H318 10<= % (w/w) <25: Eye Irrit. 2 - H319

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxic	Genus	
Formic acid	LD50 oral	730 mg/kg	Rat
	LD50 dermal	Not relevant	
EC: 200-579-1	LC50 inhalation vapour	7.85 mg/L	Rat

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

## By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

### By skin contact:

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 2/13

<sup>(2)</sup> Substance with a Union workplace exposure limit

#### Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

## IF Maxid Silage L - F0062 - A00124 - A00190



#### SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

#### Unsuitable extinguishing media:

Water jet

## 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

## For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

## For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) **Page 3/13** 

#### Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

#### 6.4 Reference to other sections:

See sections 8 and 13.

#### **SECTION 7: HANDLING AND STORAGE**

## 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 0 °C

Maximum Temp.: 40 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

	Identification	Occupational exposure limits			
propionic acid		WEL (8h)	10 ppm	31 mg/m <sup>3</sup>	
CAS: 79-09-4	EC: 201-176-3	WEL (15 min)	15 ppm	46 mg/m <sup>3</sup>	
Formic acid		WEL (8h)	5 ppm	9.6 mg/m <sup>3</sup>	
CAS: 64-18-6	EC: 200-579-1	WEL (15 min)			
Acetic acid		WEL (8h)	10 ppm	25 mg/m <sup>3</sup>	
CAS: 64-19-7	EC: 200-580-7	WEL (15 min)	20 ppm	50 mg/m <sup>3</sup>	

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 4/13



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Formic acid	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64-18-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 200-579-1	Inhalation	Not relevant	Not relevant	Not relevant	9.5 mg/m <sup>3</sup>
Acetic acid	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64-19-7	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 200-580-7	Inhalation	Not relevant	25 mg/m³	Not relevant	25 mg/m³

### **DNEL (General population):**

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Formic acid	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 64-18-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 200-579-1	Inhalation	Not relevant	Not relevant	Not relevant	3 mg/m³	
Acetic acid	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 64-19-7	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 200-580-7	Inhalation	Not relevant	25 mg/m <sup>3</sup>	Not relevant	25 mg/m <sup>3</sup>	

#### **PNEC:**

Identification				
Formic acid	STP	7.2 mg/L	Fresh water	2 mg/L
CAS: 64-18-6	Soil	1.5 mg/kg	Marine water	0.2 mg/L
EC: 200-579-1	Intermittent	1 mg/L	Sediment (Fresh water)	13.4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	1.34 mg/kg
Acetic acid	STP	85 mg/L	Fresh water	3.058 mg/L
CAS: 64-19-7	Soil	0.47 mg/kg	Marine water	0.306 mg/L
EC: 200-580-7	Intermittent	30.58 mg/L	Sediment (Fresh water)	11.36 mg/kg
	Oral	Not relevant	Sediment (Marine water)	1.136 mg/kg

## 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

## C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Butyl, Breakthrough time: > 480 min, Thickness: 0.7 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	CAT III	EN 13034:2005+A1:2009 UNE-EN ISO 18526-1 al 4:2020 EN ISO 13982- 1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	CAT III	EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>→</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 56.3 % weight

V.O.C. density at 20 °C: 684.72 kg/m³ (684.72 g/L)

Average carbon number: 2.08

Average molecular weight: 61.19 g/mol

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\*

## 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### **Appearance:**

Physical state at 20 °C:

Appearance:

Colourless

Colour:

Yellowish

Odour:

Pungent

Odour threshold:

Not relevant \*\*

Volatility:

Boiling point at atmospheric pressure: 117 °C Vapour pressure at 20 °C: 2474 Pa

\*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 6/13

<sup>\*\*</sup> Changes with regards to the previous version



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\* (continued)

Vapour pressure at 50 °C: 11150.59 Pa (11.15 kPa)

Evaporation rate at 20 °C: Not relevant \*

**Product description:** 

Density at 20 °C: 1216.2 kg/m3

Relative density at 20 °C: 1.216 Dynamic viscosity at 20 °C: 2.31 mPa·s Kinematic viscosity at 20 °C: 1.9 mm<sup>2</sup>/s Kinematic viscosity at 40 °C: Not relevant \* Not relevant \* Concentration: pH: ca. 3 (at 10 %) Vapour density at 20 °C: Not relevant \* Partition coefficient n-octanol/water 20 °C: Not relevant \* Solubility in water at 20 °C: Not relevant \* Solubility properties: Not relevant \*

Decomposition temperature: Not relevant \*

Not relevant \* Melting point/freezing point:

Flammability:

>61 °C Flash Point:

Flammability (solid, gas): Not relevant \*

Autoignition temperature: 421 °C

Lower flammability limit: Not relevant \* Not relevant \* Upper flammability limit:

**Particle characteristics:** 

Median equivalent diameter: Not relevant \*

#### 9.2 Other information:

### Information with regard to physical hazard classes:

Explosive properties: Not relevant \* Oxidising properties: Not relevant \* Corrosive to metals: Not relevant \* Heat of combustion: Not relevant \* Aerosols-total percentage (by mass) of flammable Not relevant \*

components:

Other safety characteristics:

Surface tension at 20 °C: Not relevant \* Not relevant \* Refraction index:

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 7/13

<sup>\*\*</sup> Changes with regards to the previous version



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 10: STABILITY AND REACTIVITY (continued)

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

## 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Corrosive to the respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
    - IARC: Not relevant
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Not relevant

## Specific toxicology information on the substances:

Identification	Acute	Acute toxicity		
Formic acid	LD50 oral	730 mg/kg	Rat	
CAS: 64-18-6	LD50 dermal	>2000 mg/kg		
EC: 200-579-1	LC50 inhalation vapour	7.85 mg/L	Rat	
propionic acid	LD50 oral	3455 mg/kg		
CAS: 79-09-4	LD50 dermal	>2000 mg/kg		
EC: 201-176-3	LC50 inhalation vapour	>20 mg/L		
Acetic acid	LD50 oral	>2000 mg/kg	T	
CAS: 64-19-7 EC: 200-580-7	LD50 dermal	>2000 mg/kg		
	LC50 inhalation vapour	>20 mg/L	1	

## 11.2 Information on other hazards:

## **Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

#### Other information

Not relevant

## **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

## 12.1 Toxicity:

## **Acute toxicity:**

Identification	Concentration		Species	Genus
Formic acid	LC50	130 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 64-18-6	EC50	Not relevant	Daphnia magna	Crustacean
EC: 200-579-1	EC50	Not relevant		
Acetic acid	LC50	75 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 64-19-7	EC50	47 mg/L (24 h)	Daphnia magna	Crustacean
EC: 200-580-7	EC50	Not relevant		

## **Chronic toxicity:**

Identification	Concentration		Species	Genus
Formic acid	NOEC	Not relevant		
CAS: 64-18-6 EC: 200-579-1	NOEC	100 mg/L	Daphnia magna	Crustacean
Acetic acid	NOEC	57.2 mg/L	Oncorhynchus mykiss	Fish
CAS: 64-19-7 EC: 200-580-7	NOEC	80 mg/L	Daphnia magna	Crustacean

## 12.2 Persistence and degradability:

## **Substance-specific information:**

Identification	Degradability		Biodegradability	
Formic acid	BOD5	Not relevant	Concentration	18 mg/L
CAS: 64-18-6	COD	Not relevant	Period	28 days
EC: 200-579-1	BOD5/COD	Not relevant	% Biodegradable	97 %

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 9/13



## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Acetic acid	BOD5	Not relevant	Concentration	100 mg/L
CAS: 64-19-7	COD	Not relevant	Period	14 days
EC: 200-580-7	BOD5/COD	Not relevant	% Biodegradable	74 %

#### 12.3 Bioaccumulative potential:

#### **Substance-specific information:**

Identification	Bioaccumulation potential		
Formic acid	BCF	3.2	
CAS: 64-18-6	Pow Log		
EC: 200-579-1	Potential	Low	
Acetic acid	BCF	3	
CAS: 64-19-7	Pow Log	-0.71	
EC: 200-580-7	Potential	Low	

## 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
propionic acid	Koc	Not relevant	Henry	Not relevant
CAS: 79-09-4	Conclusion	Not relevant	Dry soil	Not relevant
EC: 201-176-3	Surface tension	2.62E-2 N/m (25 °C)	Moist soil	Not relevant
Formic acid	Koc	31	Henry	1.9E-2 Pa·m³/mol
CAS: 64-18-6	Conclusion	Very High	Dry soil	Not relevant
EC: 200-579-1	Surface tension	3.862E-2 N/m (25 °C)	Moist soil	Not relevant
Acetic acid	Koc	Not relevant	Henry	Not relevant
CAS: 64-19-7	Conclusion	Not relevant	Dry soil	Not relevant
EC: 200-580-7	Surface tension	2.699E-2 N/m (25 °C)	Moist soil	Not relevant

#### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

### 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

#### 12.7 Other adverse effects:

Not described

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 14*	Acids	Hazardous

## Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP8 Corrosive

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## **SECTION 14: TRANSPORT INFORMATION**

## NDUFARM

### Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 14: TRANSPORT INFORMATION (continued)

#### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

14.1 UN number or ID number: UN3265

14.2 UN proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Formic acid;

propionic acid)

14.3 Transport hazard class(es):

Labels:

Π 14.4 Packing group: 14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 274 Tunnel restriction code: F

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Maritime transport in bulk

according to IMO instruments:

Not relevant

### Transport of dangerous goods by sea:

With regard to IMDG 41-22:

14.1 UN number or ID number: UN3265

14.2 UN proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Formic acid;

propionic acid)

14.3 Transport hazard class(es): 8

8 Labels: 14.4 Packing group: П No

14.5 Marine pollutant: 14.6 Special precautions for user

> Special regulations: 274

EmS Codes: F-A, S-B Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: SGG1 14.7 Maritime transport in bulk

according to IMO

instruments:

Not relevant

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



14.1 UN number or ID number: UN3265

14.2 UN proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Formic acid;

propionic acid)

14.3 Transport hazard class(es):

Labels: 8

14.4 Packing group: Π 14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Maritime transport in bulk

according to IMO

instruments:

Not relevant

## **SECTION 15: REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains benzoic acid, Hexa-2,4-dienoic acid.

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 11/13

#### Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

## IF Maxid Silage L - F0062 - A00124 - A00190



#### SECTION 15: REGULATORY INFORMATION (continued)

- Article 95, REGULATION (EU) No 528/2012: Formic acid (64-18-6) PT: (2,3,4,5,6); benzoic acid (65-85-0) PT: (3,4,7,9); Hexa-2,4-dienoic acid (110-44-1) PT: (6)
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

#### Seveso III:

Not relevant

## Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION \*\*

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

## Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Hazard statements

Information on basic physical and chemical properties (SECTION 9):

· Flash Point

## Texts of the legislative phrases mentioned in section 2:

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H314: Causes severe skin burns and eye damage.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

STOT SE 3: H335 - May cause respiratory irritation.

#### Classification procedure:

Eye Dam. 1: Calculation method STOT SE 3: Calculation method Skin Corr. 1B: Calculation method **Advice related to training:** 

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 12/13

<sup>\*\*</sup> Changes with regards to the previous version

### Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

## IF Maxid Silage L - F0062 - A00124 - A00190



## SECTION 16: OTHER INFORMATION \*\* (continued)

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

## **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Date of compilation: 4/26/2022 Revised: 4/21/2025 Version: 2 (Replaced 1) Page 13/13

<sup>\*\*</sup> Changes with regards to the previous version